IRON ATTACH

IA-JB-60T

FORKLIFT & TELEHANDLER TELESCOPING JIB BOOM

6,000 lb Capacity | 12 ft Reach

SCAN FOR PRICE AND A DELIVERED QUOTE

or visit ironattach.com

Place loads beyond the reach of your forks. Slides onto your existing forks with nine rated lifting positions and up to 12 ft of reach.



6,000 LB MAX, POS 1 TO 4 | **2,100 LB** AT FULL 12 FT | **465 LB** WEIGHT

- **Stop rigging off the fork tips. An engineered lift point, rated and marked.**
- **Slides onto the forks you already own. No carriage swap, no forks to remove.**
- **Clearly marked attachment ratings at every hook position.**

SAFETY-FIRST ENGINEERING

- Nine rated hook positions from 24 in out to 144 in
- Rated load clearly marked at every hook position
- Laser-cut alignment markings for positive pin engagement
- Scan the decal for the IA Technical Hub: allowable load from your machine's own chart, operating instructions, video guides, and an AI assistant on call any hour.
- Retaining pins behind the fork heels plus a safety chain to the carriage
- Low 11.5 in profile for better visibility over the load and flat storage

DURABILITY

- Heavy-duty 2-section tubular steel construction with continuous welds
- Plascoat exterior coating for abrasion and corrosion resistance
- Load tested and working in the field, 3-year structural warranty



Rated load plate, position marks, and QR decal



Fork pockets seated on the forks, with retaining pins

Request a quote, or send us your machine and fork size and we will confirm the fit: ironattach.com



SPECIFICATIONS

Specification	Value
Model	IA-JB-60T
Rated Capacity	Up to 6,000 lb (2,100 lb at full extension)
Hook Positions	9 (4 fixed, 5 telescoping)
Load Center Range	24 in - 144 in (2 ft - 12 ft)
Length Retracted	103 in (8 ft 7 in)
Length Extended	151 in (12 ft 7 in)
Width	3 ft 3 1/2 in
Height	11.5 in
Weight	465 lb
Fork Pocket Inside Dimensions	7.63 in (W) x 3.63 in (H)
Fork Pocket Length	44 in
Fork Pocket Spacing	30 in center-to-center, fixed
Fork Pocket Span	22.38 in inside, 37.63 in outside
Fork Retention	Retaining pins behind fork heels
Safety Retention	Safety chain to carriage anchor points
Hook and Shackle	3/4 in bolted shackle and heavy-duty swivel hook (one included)
Construction	2-section tubular steel, continuous welds
Finish	Plascoat, Anthracite Grey
Warranty	3-year structural, 1-year components
Country of Origin	USA

RATED CAPACITY BY HOOK POSITION

Position	Load Center	Max Load
Position 1 (fixed boom)	24 in	6,000 lb
Position 2 (fixed boom)	48 in	6,000 lb
Position 3 (fixed boom)	66 in	6,000 lb
Position 4 (fixed boom)	84 in	6,000 lb
Position 5 (telescoping)	96 in	5,800 lb
Position 6 (telescoping)	108 in	5,000 lb
Position 7 (telescoping)	120 in	3,800 lb
Position 8 (telescoping)	132 in	2,700 lb
Position 9 (telescoping, full 12 ft)	144 in	2,100 lb

Structural capacity of the attachment only, not host machine capacity. Obtain official down-rated capacity from the lift truck manufacturer.

Designed to meet ASME BTH-1-2023 and ASME B30.20, with ANSI/ITSDF B56.6 and applicable OSHA requirements addressed in the design. Every rating carries a 3 to 1 design margin. Validated by engineering analysis and physical load testing.

Need a quote, or not sure it fits your machine?

Request a quote at ironattach.com. Scan for the operator manual and the load calculator that gives you the allowable load on your own machine.

go.ironattach.com/IAJB60Tss